

RoHS Compliant Product

A suffix of "C" specifies halogen free

FEATURES


- Trench Barrier Schottky technology
- Low forward voltage drop
- Low reverse current
- High current capability
- High reliability
- High surge current capability
- Epitaxial construction

MECHANICAL DATA

- Case: Molded plastic
- Epoxy: UL94V-0 rate flame retardant
- Lead: Lead solderable per MIL-STD-202 method 208 guaranteed
- Polarity: As Marked
- Mounting position: Any

ORDER INFORMATION

Part Number	Type
SBL30A100F	Lead (Pb)-free
SBL30A100F-C	Lead (Pb)-free and Halogen-free



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	14.50	16.50	H	2.70	4.35
B	9.50	10.72	J	0.90	1.70
C	12.60	14.22	K	0.30	0.95
D	4.20	5.10	L	2.34	2.75
E	2.30	3.30	M	2.40	3.60
F	2.30	3.10	N	Ø 3.0	Ø 3.8
G	0.30	0.75			

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Rating 25°C ambient temperature unless otherwise specified. Single phase half wave, 60Hz, resistive or inductive load.
For capacitive load, de-rate current by 20%).

Parameter	Symbol	Ratings		Unit
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	100		V
Working Peak Reverse Voltage	V_{RSM}	100		V
Maximum DC Blocking Voltage	V_{DC}	100		V
Maximum Average Forward Rectified Current (Per Leg)	I_F	15		A
		30		
Peak Forward Surge Current, 8.3ms single half sine-wave Superimposed on rated load (JEDEC method)	I_{FSM}	150		A
Voltage Rate of Change (Rated V_R)	dv/dt	10000		V/ μ s
Typical Thermal Resistance	$R_{\theta JC}$	4		°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	150, -55~150		°C

ELECTRICAL CHARACTERISTICS


Parameter	Symbol	Typ.	Max.	Unit	Test Conditions
Maximum Instantaneous Forward Voltage	V_F	0.48	0.52	V	$I_F=3A, T_J=25^\circ C$
		0.54	0.58		$I_F=5A, T_J=25^\circ C$
		0.69	0.72		$I_F=10A, T_J=25^\circ C$
		0.8	0.84		$I_F=15A, T_J=25^\circ C$
		0.7	-		$I_F=15A, T_J=125^\circ C$
Maximum DC Reverse Current @Rated DC Blocking Voltage ²	I_R	-	0.1	mA	$T_J=25^\circ C$
		-	10		$T_J=100^\circ C$
Typical Junction Capacitance ¹	C_J	470	-	pF	

Notes:


1. Measured at 1MHz and applied reverse voltage of 5V D.C.
2. Pulse Test: Pulse Width=300μs, Duty Cycle≤2%.

RATINGS AND CHARACTERISTIC CURVES


Typical Forward Current Derating Curve




Typical Junction Capacitance (pF)



Maximum Non-Repetitive Forward Surge Current



Typical Forward Characteristic



Typical Reverse Characteristic

