


RoHS Compliant Product
A suffix of "C" specifies halogen free

FEATURES

- Schottky Barrier chip
- High thermal reliability
- Patented Super Barrier Rectifier Technology
- High forward surge capability
- Ultra low power loss and high efficiency
- Excellent high temperature stability
- Plastic material-UL flammability 94V-0

PACKAGE INFORMATION

| Package | MPQ | Leader Size |
|---------|-----|-------------|
| TO-277D | 5K | 13 inch |



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(T_A=25°C, unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, de-rate current by 20%).)

| Parameter | Symbol | Rating | | Unit |
|--|-----------------------------------|--------------|--|--------|
| Maximum Recurrent Peak Reverse Voltage | V _{RRM} | 60 | | V |
| Working Peak Reverse Voltage | V _{RSM} | 60 | | V |
| Maximum DC Blocking Voltage | V _{DC} | 60 | | V |
| Maximum Average Forward Rectified Current | I _F | 20 | | A |
| Peak Forward Surge Current, 8.3 ms single half sine-wave Superimposed on rated load (JEDEC method) | I _{FSM} | 250 | | A |
| Voltage Rate of Change (Rated V _R) | dv/dt | 10000 | | V / μs |
| Typical Thermal Resistance from Junction to Ambient | R _{θJA} | 80 | | °C / W |
| Typical Thermal Resistance from Junction to Lead | R _{θJL} | 5 | | °C / W |
| Operating and Storage Temperature Range | T _J , T _{STG} | 150, -55~150 | | °C |

ELECTRICAL CHARACTERISTICS


| Parameter | Symbol | Typ. | Max. | Unit | Test Condition |
|--|----------------|------|------|------|--|
| Maximum Instantaneous Forward Voltage | V _F | 0.37 | 0.39 | V | I _F =3A, T _J =25°C |
| | | 0.41 | 0.46 | | I _F =5A, T _J =25°C |
| | | 0.49 | 0.53 | | I _F =10A, T _J =25°C |
| | | 0.65 | 0.7 | | I _F =20A, T _J =25°C |
| | | 0.62 | - | | I _F =20A, T _J =125°C |
| Maximum DC Reverse Current at Rated DC Blocking Voltage ² | I _R | - | 0.5 | mA | T _J =25°C |
| | | - | 20 | | T _J =100°C |
| Typical Junction Capacitance ¹ | C _J | 520 | - | pF | |

Notes:


1. Measured at 1MHz and applied reverse voltage of 5.0V D.C.
2. Pulse Test : Pulse Width = 300 μs, Duty Cycle ≤ 2.0%.

RATINGS AND CHARACTERISTIC CURVES


Typical Forward Current Derating Curve




Typical Junction Capacitance



Maximum Non-Repetitive Forward Surge Current



Typical Forward Characteristic



Typical Reverse Characteristic

