

RoHS Compliant Product
A suffix of "-C" specifies halogen free


FEATURES

- Soft Reverse Recovery Diodes
- 150°C Operating Junction Temperature
- Fast Switching for High Efficiency
- Low Forward Voltage, High Current Capability
- Plastic Material Used Carries Underwriters Laboratory Flammability Classification 94V-0

ORDER INFORMATION

Part Number	Type
SFL1660	Lead (Pb)-free
SFL1660-C	Lead (Pb)-free and Halogen-free

TO-220A



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	14.68	15.50	H	3.57	4.20
B	9.7	10.4	J	-	1.30
C	13.06	14.62	K	0.72	0.96
D	4.22	4.98	L	4.84	5.32
E	1.14	1.38	M	2.48	2.98
F	2.20	2.98	N	Ø 3.7	Ø 3.9
G	0.27	0.55	O	1.12	1.37

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Rating 25°C ambient temperature unless otherwise specified. Single phase half wave, 60Hz, resistive or inductive load.
For capacitive load, de-rate current by 20%).


Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V _{RRM}	600	V
Working Peak Reverse Voltage	V _{RWM}	600	V
DC Blocking Voltage	V _R	600	V
Average Rectifier Forward Current	I _{F(AV)}	16	A
Non-Repetitive Peak Surge Current @ Surge applied at rate load conditions half-wave, single phase, 60Hz	I _{FSM}	120	A
Max. Instantaneous Forward Voltage @ I _F =16A	T _A =25°C	V _F	1.35
	T _A =125°C		1.3
Max. Instantaneous Reverse Current ²	T _A =25°C	I _R	0.1
	T _A =125°C		1
Reverse Recovery Time ³	T _{RR}	100	nS
Typical Junction Capacitance ¹	C _J	82	pF
Thermal Resistance	R _{θJC}	2	°C/W
Operating Junction and Storage Temperature Range	T _J , T _{STG}	150, -55~150	°C

Notes:


1. Measured at 1MHz and applied reverse voltage of 4V D.C.
2. Pulse Test: Pulse Width=300μs, Duty Cycle≤2%.
3. I_F=0.5A, I_R=1A, I_{RR}=0.25A.

RATINGS AND CHARACTERISTIC CURVES


Typical Forward Current Derating Curve




Maximum Non-Repetitive Forward Surge Current



Typical Junction Capacitance



Typical Forward Characteristic



Typical Reverse Characteristic

